



**CHASE** Construction Products  
**MATERIAL SAFETY DATA SHEET**

**Product:** Rosphalt 50 LT

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**MANUFACTURED BY:** CHASE CORPORATION PITTSBURGH  
201 ZETA DRIVE  
PITTSBURGH, PA 15238

**GENERAL INFORMATION:** (412) 828-1500

**EMERGENCY, CHEMTREC:** 800-424-9300, Only in the event of chemical emergencies involving a spill, leak, fire, exposure or any accident involving chemicals. Outside USA: 01(703) 527-3887

**REVISION DATE:** 09/1710

**PREPARED BY:** B.RADMARD

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>CAS NUMBER</u>	<u>IDENTIFICATION</u>	<u>APP. % BY WGT.</u>
64742-52-5	Severely Hydrated Heavy Naphthenic Distillate	30-40
7440-44-0	Carbon	20-30
Trade Secret	Additive	5-10
Trade Secret	Additive	5-10

**3. HAZARDOUS IDENTIFICATION**

**HAZARDOUS POLYMERIZATION:** Will Not Occur

**ROUTES OF EXPOSURE:** Inhalation, Skin, Eyes and Ingestion.

IMMEDIATE EFFECTS:

**INHALATION:** Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat.

**SKIN CONTACT:** Normally not irritating. If rash develops or irritation persists, seek physician.

**EYE CONTACT:** If eye contact is made and irritation develops, contact physician.

**INGESTION:** Due to nature of product ingestion is not likely. If ingested, see physician.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

**ACCUTE:** Inhalation – exposure during hot process may cause respiratory. Eye or nose irritation.

**CHRONIC:** Inhalation – Long term exposure to concentrated hot processing fumes may reduce lung function and cause chronic bronchitis

**4. FIRST AID MEASURES**

**GENERAL ADVICE:**

**INHALATION:** Due to the nature of the product, there is no inhalation hazard. Heated vapors may cause irritation of nasal passages and throat. If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, **GET MEDICAL ATTENTION.**



**CHASE** Construction Products

## MATERIAL SAFETY DATA SHEET

SKIN CONTACT: Normally not irritating. If rash develops or irritation persists, seek physician.

EYE CONTACT: Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, **GET MEDICAL ATTENTION.**

INGESTION: Due to nature of product ingestion is not likely. If ingested, see physician.

### 5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon Dioxide or dry chemical. If entering a confined area, use self-contained breathing apparatus if applicable

EXPLOSION DATA:

SENSITIVITY TO MECHANICAL IMPACT: Stable.

SENSITIVITY TO STATIC DISCHARGE: Stable.

### 6. ACCIDENTAL RELEASE MEASURES

PRECAUTIONS FOR PERSONNEL: No special clothes are required, but do wear gloves.

ENVIRONMENTAL PRECAUTIONS: No special procedures normally needed.

PROCESS FOR CLEANING: Absorb with inert material. Remove sources of ignition. Scoop material with non-sparking tools.

### 7. HANDLING AND STORAGE

HANDLING: Avoid direct contact with product. No special ventilation required.

STORAGE: Store away from ignition sources and open flames.

### 8. EXPOSURE RESTRICTIONS AND PERSONAL PROTECTION

MATERIALS WITH LIMITS THAT REQUIRE SUPERVISION:

CAS NUMBER	IDENTIFICATION	APP. % BY WGT.	NIOSH REL	VALUE	UNIT
64742-52-5	Hydrated Heavy Naphthenic Distillate	30-40	TWA	5.0	mg/m <sup>3</sup>
7440-44-0	Carbon	20-30	TWA	2.4	mg/m <sup>3</sup>
Trade Secret	Additive	5-10	TWA	15	mg/m <sup>3</sup>
Trade Secret	Additive	5-10	TWA	15	mg/m <sup>3</sup>

ADDITIONAL ADVICE: No special clothes are required, but do wear gloves.

### 9. PHYSICAL PROPERTIES

ODOR: AROMATIC

CHANGE OF STATE	VALUE/AREA	UNIT	METHOD
FREEZING POINT:	N/A	°C	
BOILING POINT:	N/A	°C (°F)	
FLASH POINT:	> 260 ( 500 )	°C (°F)	TCC
IGNITION TEMPERATURE:			
SPECIFIC GRAVITY:	0.992	H <sub>2</sub> O = 1	



## MATERIAL SAFETY DATA SHEET

% VOLATILE BY VOLUME: Nil %  
 SOLUBILITY IN WATER: Insoluble  
 PH VALUE: N/A  
 VISCOSITY: CPS  
 FLAMMABLE LIMITS: LEL N/A UEL N/A  
 EVAPORATION RATE: N/A BUAC = 1

### 10. STABILITY AND REACTIVITY

**STABILITY:** Stable  
**CONDITIONS TO AVOID:** Open Flame.  
**MATERIALS TO AVOID:** None known  
**DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.  
**EYES:** Remove contact lenses. Flush eyes with large amounts of water, preferably lukewarm water, for at least 15 minutes. If irritation persists, **GET MEDICAL ATTENTION.**  
**SKIN:** If solid product gets on the skin, wash the contaminated skin with soap and water. If irritation develops or persists after the area has been washed. Should molten material strike the skin, flush with cold water. Thoroughly wash exposed area with mineral oil and flush with water. **GET MEDICAL ATTENTION.**  
**INHALATION:** If a person breathes large amounts of heated product vapors, move the exposed person to fresh air at once. If breathing difficult, **GET MEDICAL ATTENTION.**  
**CONSUMPTION:** If swallowed, call physician immediately. Only induce vomiting at the instructions of a physician. **DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.**

### 11. TOXICOLOGICAL INFORMATION

CAS NUMBER	IDENTIFICATION	DERMAL	INAHALATION	ORAL
		LD50	LC50	LD50
64742-52-5	Hydrated Heavy Naphthenic Distillate	N/E	N/E	N/E
7440-44-0	Carbon	N/E	N/E	N/E
Trade Secret	Additive	N/E	N/E	N/E
Trade Secret	Additive	N/E	N/E	N/E

CAS NUMBER	IDENTIFICATION	CARCINOGENICITY		TERATOGENICITY	MUTAGENICITY
		ACGIH	IARC		
64742-52-5	Hydrated Heavy Naphthenic Distillate	N/E	N/E	N/E	N/E
7440-44-0	Carbon	N/E	N/E	N/E	N/E
Trade Secret	Additive	N/E	N/E	N/E	N/E
Trade Secret	Additive	N/E	N/E	N/E	N/E

### 12. ECOLOGICAL INFORMATION

VOLATILE ORGANIC COMPOUNDS: 0 Grams Per Liter (g/l). 0 Pounds Per Gallon (lb/g).

### 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be made in accordance with Federal, State and Local regulations.

### 14. TRANSPORT INFORMATION



**CHASE** Construction Products  
**MATERIAL SAFETY DATA SHEET**

SHIPPING CLASS: Not Regulated

---

**15. REGULATORY INFORMATION**

SARA SECTION 302:

SARA (311,312) HAZARD CLASS:

SARA (313) CHEMICALS: NONE

CERCLA: N/A

CPSC CLASSIFICATION:

HMIS: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 0

NFPA: FLAMMABILITY: 1 REACTIVITY: 0 HEALTH: 0

CALIFORNIA PROPOSITION 65:

- A. This product contains a chemical known to the State of CA to cause birth defects or other reproductive harm.
  - B. This product contains a chemical known to the State of CA to cause cancer.
  - C. This product contains a chemical known to the State of CA to cause cancer and birth defects or other reproductive harm.
- 

**16. OTHER INFORMATION**

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND ARE NOT A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED IS MADE. THE STATED RECOMMENDED HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE.

C = Ceiling Limit, NEGL = Negligible, N/A = Not Applicable, N/E = Not Established, PROP. = Proprietary.

---