

DESCRIPTION

CONCRETE AND BRICK WATER REPELLENT (SILANE-SILOXANE 15%) is a clear solvent-based solution formulated for use on concrete and brick as well as other masonry surfaces to provide a water repellent natural finish. The 43 solution flows like water and is used to achieve deep surface penetration. It can be applied to concrete, precast concrete, stucco, ornamental stone, terra cotta, artificial exterior products, brick walls.

FEATURES

- ▶ Water repellency protection.
- ▶ Retains and enhances natural finish.
- ▶ Deep penetration of surface.
- ▶ Non-gloss finish.
- ▶ 15% solids content.
- ▶ Will not flake, peel or crack.
- ▶ Allows surface to breathe.
- ▶ Significantly reduces problems associated with deterioration, efflorescence, mildew, staining, rebar corrosion and freeze/thaw damage.
- ▶ Effective protection for brick, block, mortar, stucco and concrete.
- ▶ Water repellent qualities within 12 to 24 hours.
- ▶ Within 5-7 days the chemical reaction is essentially completed and the surface and substrate is water repellent

APPLICATION

Surface has to be clean and dry for proper bonding. Remove dirt, grease, oil, efflorescence film and other foreign material from surface. Apply Miton 43 working from top to bottom using a brush, roller or low pressure sprayer.

SHELF LIFE

1 year from date of manufacture

CURING

Apply between 5°C and 35°C. Allow 24 hours with no rain for proper cure.

CLEANUP

Remove with mineral spirits product. Wear proper personal protective equipment when doing so. Spot test before large area removals.



LIMITATIONS

Do not apply Immediately after rain.
Surface must be dry for 24 hours.

COVERAGE

Approximate depending upon surface conditions and porosity.

Smooth surfaces	150 sq.ft. per gal.
Porous / Rough surfaces	80-125 sq.ft. per gal.

PACKAGING

18.9 litre (5 gallon) pail.
200 litre drum

PRECAUTIONS

Contains petroleum distillates.
Keep out of reach of children.
Keep away from heat and open flame.
Provide proper ventilation for storage and application.
Follow proper trade application practises.
Protect eyes and skin. In case of contact, flush thoroughly with clean water for 15 minutes. Harmful or fatal if swallowed.

Refer to MSDS for additional handling and care information.

FOR INDUSTRIAL USE ONLY

The information and recommendations provided in the document are given in good faith with an understanding that it is provided based on Canadian Construction Products experience with the product, handled and cared for under normal conditions, and used within the shelf life of the product. No warranty of its suitability for any particular purpose is provided due to variability of site conditions during installation. No liability arising from a legal relationship shall be incurred by Canadian Construction Products from the product information provided, recommendations, or any other advice offered. Please check ccpcanada.com for the most recent product information or request a copy from our offices.



CANADIAN CONSTRUCTION PRODUCTS

#4 19747 Telegraph Trail, Langley B.C. V1M 3E6

TEL: 604.888.7171
FAX: 604.888.8191
info@ccpcanada.com

Copyright 2005 Infratech Polymers Inc. dba Canadian Construction Products. All rights reserved. The Canadian Construction Products name and logo, and all related product and service names, design marks and slogans are the trademarks or registered trademarks of Canadian Construction Products. All other product and service marks contained herein are the trademarks of their respective owners. You may not use any Canadian Construction Products or third party trademarks or logos without the prior written consent of Canadian Construction Products or the applicable trademark owner.